



F2-RB19 Inch Threads

Bonding Fasteners

Rotaloc International, LLC

Sample Image



As Shown: F2-RB19-8-32x0.375

F2




Female Threaded Collar

RB19


19 Millimeter Round Baseplate

Example - Part Number

F2-RB19-8-32x0.375



Open (Thru)



Closed (Blind)

Thread	Common Thread Lengths - Inch									
4-40	0.250	0.375	0.500	0.625	0.750	0.875	1.000	1.250	1.500	2.000
6-32	0.250	0.375	0.500	0.625	0.750	0.875	1.000	1.250	1.500	2.000
8-32	0.250	0.375	0.500	0.625	0.750	0.875	1.000	1.250	1.500	2.000
10-24	0.250	0.375	0.500	0.625	0.750	0.875	1.000	1.250	1.500	2.000
10-32	0.250	0.375	0.500	0.625	0.750	0.875	1.000	1.250	1.500	2.000
1/4-20	0.250	0.375	0.500	0.625	0.750	0.875	1.000	1.250	1.500	2.000
1/4-28	0.250	0.375	0.500	0.625	0.750	0.875	1.000	1.250	1.500	2.000
5/16-18	0.250	0.375	0.500	0.625	0.750	0.875	1.000	1.250	1.500	2.000
3/8-16	0.250	0.375	0.500	0.625	0.750	0.875	1.000	1.250	1.500	2.000
7/16-20	0.250	0.375	0.500	0.625	0.750	0.875	1.000	1.250	1.500	2.000
1/2-13	0.250	0.375	0.500	0.625	0.750	0.875	1.000	1.250	1.500	2.000
5/8-11	0.250	0.375	0.500	0.625	0.750	0.875	1.000	1.250	1.500	2.000
3/4-10	0.250	0.375	0.500	0.625	0.750	0.875	1.000	1.250	1.500	2.000

* Grayed-out sizes are not recommended with shown baseplate

Plating	TZP (Trivalent Zinc)	Zinc-Nickel	Nano	E-Coat	Grades	303	304	316
Other plating and coating options available					* Grayed-out sizes are not recommended with shown baseplate			

All plating and materials offered are RoHS and REACH Compliant

Availability

Many common sizes in stock. Call for availability.

A Rotaloc® Representative will be happy to discuss your specific application and product specifications.

Contact Rotaloc®

Contact Us:

Tel (303) 948-5434 or Toll Free (888) Rotaloc or (888)-768-2562
www.rotaloc.com | info@rotaloc.com

Address

Rotaloc International, LLC
 9903 Titan Court, Suite #15, Littleton, CO 80125 - USA

Value - Quality - Service



F2-RB23 Inch Threads

Bonding Fasteners

Rotaloc International, LLC

Sample Image



As Shown: F2-RB23-1/4-20x0.500

F2




Female Threaded Collar

RB23


23 Millimeter Round Baseplate

Example - Part Number

F2-RB23-1/4-20x0.500



Open (Thru)



Closed (Blind)

Thread	Common Thread Lengths - Inch									
4-40	0.250	0.375	0.500	0.625	0.750	0.875	1.000	1.250	1.500	2.000
6-32	0.250	0.375	0.500	0.625	0.750	0.875	1.000	1.250	1.500	2.000
8-32	0.250	0.375	0.500	0.625	0.750	0.875	1.000	1.250	1.500	2.000
10-24	0.250	0.375	0.500	0.625	0.750	0.875	1.000	1.250	1.500	2.000
10-32	0.250	0.375	0.500	0.625	0.750	0.875	1.000	1.250	1.500	2.000
1/4-20	0.250	0.375	0.500	0.625	0.750	0.875	1.000	1.250	1.500	2.000
1/4-28	0.250	0.375	0.500	0.625	0.750	0.875	1.000	1.250	1.500	2.000
5/16-18	0.250	0.375	0.500	0.625	0.750	0.875	1.000	1.250	1.500	2.000
3/8-16	0.250	0.375	0.500	0.625	0.750	0.875	1.000	1.250	1.500	2.000
7/16-20	0.250	0.375	0.500	0.625	0.750	0.875	1.000	1.250	1.500	2.000
1/2-13	0.250	0.375	0.500	0.625	0.750	0.875	1.000	1.250	1.500	2.000
5/8-11	0.250	0.375	0.500	0.625	0.750	0.875	1.000	1.250	1.500	2.000
3/4-10	0.250	0.375	0.500	0.625	0.750	0.875	1.000	1.250	1.500	2.000

* Grayed-out sizes are not recommended with shown baseplate

Plating	TZP (Trivalent Zinc)	Zinc-Nickel	Nano	E-Coat	Grades	303	304	316
Other plating and coating options available					* Grayed-out sizes are not recommended with shown baseplate			

All plating and materials offered are RoHS and REACH Compliant

Availability

Many common sizes in stock. Call for availability.

A Rotaloc® Representative will be happy to discuss your specific application and product specifications.

Contact Rotaloc®

Contact Us:

Tel (303) 948-5434 or Toll Free (888) Rotaloc or (888)-768-2562
www.rotaloc.com | info@rotaloc.com

Address

Rotaloc International, LLC
 9903 Titan Court, Suite #15, Littleton, CO 80125 - USA

Value - Quality - Service



F2-RB32 Inch Threads

Bonding Fasteners

Rotaloc International, LLC

Sample Image



As Shown: F2-RB32-1/4-20x0.625

F2




Female Threaded Collar

RB32


32 Millimeter Round Baseplate

Example - Part Number

F2-RB32-1/4-20x0.625



Open (Thru)



Closed (Blind)

Thread	Common Thread Lengths - Inch									
4-40	0.250	0.375	0.500	0.625	0.750	0.875	1.000	1.250	1.500	2.000
6-32	0.250	0.375	0.500	0.625	0.750	0.875	1.000	1.250	1.500	2.000
8-32	0.250	0.375	0.500	0.625	0.750	0.875	1.000	1.250	1.500	2.000
10-24	0.250	0.375	0.500	0.625	0.750	0.875	1.000	1.250	1.500	2.000
10-32	0.250	0.375	0.500	0.625	0.750	0.875	1.000	1.250	1.500	2.000
1/4-20	0.250	0.375	0.500	0.625	0.750	0.875	1.000	1.250	1.500	2.000
1/4-28	0.250	0.375	0.500	0.625	0.750	0.875	1.000	1.250	1.500	2.000
5/16-18	0.250	0.375	0.500	0.625	0.750	0.875	1.000	1.250	1.500	2.000
3/8-16	0.250	0.375	0.500	0.625	0.750	0.875	1.000	1.250	1.500	2.000
7/16-20	0.250	0.375	0.500	0.625	0.750	0.875	1.000	1.250	1.500	2.000
1/2-13	0.250	0.375	0.500	0.625	0.750	0.875	1.000	1.250	1.500	2.000
5/8-11	0.250	0.375	0.500	0.625	0.750	0.875	1.000	1.250	1.500	2.000
3/4-10	0.250	0.375	0.500	0.625	0.750	0.875	1.000	1.250	1.500	2.000

* Grayed-out sizes are not recommended with shown baseplate

Plating	TZP (Trivalent Zinc)	Zinc-Nickel	Nano	E-Coat	Grades	303	304	316
Other plating and coating options available					* Grayed-out sizes are not recommended with shown baseplate			

All plating and materials offered are RoHS and REACH Compliant

Availability

Many common sizes in stock. Call for availability.

A Rotaloc® Representative will be happy to discuss your specific application and product specifications.

Contact Rotaloc®

Contact Us:

Tel (303) 948-5434 or Toll Free (888) Rotaloc or (888)-768-2562
www.rotaloc.com | info@rotaloc.com

Address

Rotaloc International, LLC
 9903 Titan Court, Suite #15, Littleton, CO 80125 - USA

Value - Quality - Service



F2-RB32#4 Inch Threads

Bonding Fasteners

Rotaloc International, LLC

Sample Image



As Shown: F2-RB32#4-1/4-20x0.500

F2




Female Threaded Collar

RB32#4


32 Millimeter Round Baseplate

Example - Part Number

F2-RB32#4-1/4-20x0.500



Open (Thru)



Closed (Blind)

Thread	Common Thread Lengths - Inch									
4-40	0.250	0.375	0.500	0.625	0.750	0.875	1.000	1.250	1.500	2.000
6-32	0.250	0.375	0.500	0.625	0.750	0.875	1.000	1.250	1.500	2.000
8-32	0.250	0.375	0.500	0.625	0.750	0.875	1.000	1.250	1.500	2.000
10-24	0.250	0.375	0.500	0.625	0.750	0.875	1.000	1.250	1.500	2.000
10-32	0.250	0.375	0.500	0.625	0.750	0.875	1.000	1.250	1.500	2.000
1/4-20	0.250	0.375	0.500	0.625	0.750	0.875	1.000	1.250	1.500	2.000
1/4-28	0.250	0.375	0.500	0.625	0.750	0.875	1.000	1.250	1.500	2.000
5/16-18	0.250	0.375	0.500	0.625	0.750	0.875	1.000	1.250	1.500	2.000
3/8-16	0.250	0.375	0.500	0.625	0.750	0.875	1.000	1.250	1.500	2.000
7/16-20	0.250	0.375	0.500	0.625	0.750	0.875	1.000	1.250	1.500	2.000
1/2-13	0.250	0.375	0.500	0.625	0.750	0.875	1.000	1.250	1.500	2.000
5/8-11	0.250	0.375	0.500	0.625	0.750	0.875	1.000	1.250	1.500	2.000
3/4-10	0.250	0.375	0.500	0.625	0.750	0.875	1.000	1.250	1.500	2.000

* Grayed-out sizes are not recommended with shown baseplate

Plating	TZP (Trivalent Zinc)	Zinc-Nickel	Nano	E-Coat	Grades	303	304	316
Other plating and coating options available					* Grayed-out sizes are not recommended with shown baseplate			

All plating and materials offered are RoHS and REACH Compliant

Availability

Many common sizes in stock. Call for availability.

A Rotaloc® Representative will be happy to discuss your specific application and product specifications.

Contact Rotaloc®

Contact Us:

Tel (303) 948-5434 or Toll Free (888) Rotaloc or (888)-768-2562
www.rotaloc.com | info@rotaloc.com

Address

Rotaloc International, LLC
 9903 Titan Court, Suite #15, Littleton, CO 80125 - USA

Value - Quality - Service



F2-RB38 Inch Threads

Bonding Fasteners

Rotaloc International, LLC

Sample Image



As Shown: F2-RB38-1/4-20x1.000

F2




Female Threaded Collar

RB38


38 Millimeter Round Baseplate

Example - Part Number

F2-RB38-1/4-20x1.000



Open (Thru)



Closed (Blind)

Thread	Common Thread Lengths - Inch									
4-40	0.250	0.375	0.500	0.625	0.750	0.875	1.000	1.250	1.500	2.000
6-32	0.250	0.375	0.500	0.625	0.750	0.875	1.000	1.250	1.500	2.000
8-32	0.250	0.375	0.500	0.625	0.750	0.875	1.000	1.250	1.500	2.000
10-24	0.250	0.375	0.500	0.625	0.750	0.875	1.000	1.250	1.500	2.000
10-32	0.250	0.375	0.500	0.625	0.750	0.875	1.000	1.250	1.500	2.000
1/4-20	0.250	0.375	0.500	0.625	0.750	0.875	1.000	1.250	1.500	2.000
1/4-28	0.250	0.375	0.500	0.625	0.750	0.875	1.000	1.250	1.500	2.000
5/16-18	0.250	0.375	0.500	0.625	0.750	0.875	1.000	1.250	1.500	2.000
3/8-16	0.250	0.375	0.500	0.625	0.750	0.875	1.000	1.250	1.500	2.000
7/16-20	0.250	0.375	0.500	0.625	0.750	0.875	1.000	1.250	1.500	2.000
1/2-13	0.250	0.375	0.500	0.625	0.750	0.875	1.000	1.250	1.500	2.000
5/8-11	0.250	0.375	0.500	0.625	0.750	0.875	1.000	1.250	1.500	2.000
3/4-10	0.250	0.375	0.500	0.625	0.750	0.875	1.000	1.250	1.500	2.000

* Grayed-out sizes are not recommended with shown baseplate

Plating	TZP (Trivalent Zinc)	Zinc-Nickel	Nano	E-Coat	Grades	303	304	316
Other plating and coating options available					* Grayed-out sizes are not recommended with shown baseplate			

All plating and materials offered are RoHS and REACH Compliant

Availability

Many common sizes in stock. Call for availability.

A Rotaloc® Representative will be happy to discuss your specific application and product specifications.

Contact Rotaloc®

Contact Us:

Tel (303) 948-5434 or Toll Free (888) Rotaloc or (888)-768-2562
www.rotaloc.com | info@rotaloc.com

Address

Rotaloc International, LLC
 9903 Titan Court, Suite #15, Littleton, CO 80125 - USA

Value - Quality - Service



F2-RB38#4 Inch Threads

Bonding Fasteners

Rotaloc International, LLC

Sample Image



As Shown: F2-RB38#4-1/4-20x1.000

F2




Female Threaded Collar

RB38#4


38 Millimeter Round Baseplate

Example - Part Number

F2-RB38#4-1/4-20x1.000



Open (Thru)



Closed (Blind)

Thread	Common Thread Lengths - Inch									
4-40	0.250	0.375	0.500	0.625	0.750	0.875	1.000	1.250	1.500	2.000
6-32	0.250	0.375	0.500	0.625	0.750	0.875	1.000	1.250	1.500	2.000
8-32	0.250	0.375	0.500	0.625	0.750	0.875	1.000	1.250	1.500	2.000
10-24	0.250	0.375	0.500	0.625	0.750	0.875	1.000	1.250	1.500	2.000
10-32	0.250	0.375	0.500	0.625	0.750	0.875	1.000	1.250	1.500	2.000
1/4-20	0.250	0.375	0.500	0.625	0.750	0.875	1.000	1.250	1.500	2.000
1/4-28	0.250	0.375	0.500	0.625	0.750	0.875	1.000	1.250	1.500	2.000
5/16-18	0.250	0.375	0.500	0.625	0.750	0.875	1.000	1.250	1.500	2.000
3/8-16	0.250	0.375	0.500	0.625	0.750	0.875	1.000	1.250	1.500	2.000
7/16-20	0.250	0.375	0.500	0.625	0.750	0.875	1.000	1.250	1.500	2.000
1/2-13	0.250	0.375	0.500	0.625	0.750	0.875	1.000	1.250	1.500	2.000
5/8-11	0.250	0.375	0.500	0.625	0.750	0.875	1.000	1.250	1.500	2.000
3/4-10	0.250	0.375	0.500	0.625	0.750	0.875	1.000	1.250	1.500	2.000

* Grayed-out sizes are not recommended with shown baseplate

Plating	TZP (Trivalent Zinc)	Zinc-Nickel	Nano	E-Coat	Grades	303	304	316
Other plating and coating options available					* Grayed-out sizes are not recommended with shown baseplate			

All plating and materials offered are RoHS and REACH Compliant

Availability

Many common sizes in stock. Call for availability.

A Rotaloc® Representative will be happy to discuss your specific application and product specifications.

Contact Rotaloc®

Contact Us:

Tel (303) 948-5434 or Toll Free (888) Rotaloc or (888)-768-2562
www.rotaloc.com | info@rotaloc.com

Address

Rotaloc International, LLC
 9903 Titan Court, Suite #15, Littleton, CO 80125 - USA

Value - Quality - Service



F2-RB38Barb Inch Threads

Bonding Fasteners

Rotaloc International, LLC

Sample Image



As Shown: F2-RB38Barb-1/4-20x1.000

F2




Female Threaded Collar

RB38Barb


38 Millimeter Round Baseplate

Example - Part Number

F2-RB38Barb-1/4-20x1.000



Open (Thru)



Closed (Blind)

Thread	Common Thread Lengths - Inch									
4-40	0.250	0.375	0.500	0.625	0.750	0.875	1.000	1.250	1.500	2.000
6-32	0.250	0.375	0.500	0.625	0.750	0.875	1.000	1.250	1.500	2.000
8-32	0.250	0.375	0.500	0.625	0.750	0.875	1.000	1.250	1.500	2.000
10-24	0.250	0.375	0.500	0.625	0.750	0.875	1.000	1.250	1.500	2.000
10-32	0.250	0.375	0.500	0.625	0.750	0.875	1.000	1.250	1.500	2.000
1/4-20	0.250	0.375	0.500	0.625	0.750	0.875	1.000	1.250	1.500	2.000
1/4-28	0.250	0.375	0.500	0.625	0.750	0.875	1.000	1.250	1.500	2.000
5/16-18	0.250	0.375	0.500	0.625	0.750	0.875	1.000	1.250	1.500	2.000
3/8-16	0.250	0.375	0.500	0.625	0.750	0.875	1.000	1.250	1.500	2.000
7/16-20	0.250	0.375	0.500	0.625	0.750	0.875	1.000	1.250	1.500	2.000
1/2-13	0.250	0.375	0.500	0.625	0.750	0.875	1.000	1.250	1.500	2.000
5/8-11	0.250	0.375	0.500	0.625	0.750	0.875	1.000	1.250	1.500	2.000
3/4-10	0.250	0.375	0.500	0.625	0.750	0.875	1.000	1.250	1.500	2.000

* Grayed-out sizes are not recommended with shown baseplate

Plating	TZP (Trivalent Zinc)	Zinc-Nickel	Nano	E-Coat	Grades	303	304	316
Other plating and coating options available					* Grayed-out sizes are not recommended with shown baseplate			

All plating and materials offered are RoHS and REACH Compliant

Availability

Many common sizes in stock. Call for availability.

A Rotaloc® Representative will be happy to discuss your specific application and product specifications.

Contact Rotaloc®

Contact Us:

Tel (303) 948-5434 or Toll Free (888) Rotaloc or (888)-768-2562
www.rotaloc.com | info@rotaloc.com

Address

Rotaloc International, LLC
 9903 Titan Court, Suite #15, Littleton, CO 80125 - USA

Value - Quality - Service



F2-RB50 Inch Threads

Bonding Fasteners

Rotaloc International, LLC

Sample Image



As Shown: F2-RB50-5/16-18x1.000

F2




Female Threaded Collar

RB50


50 Millimeter Round Baseplate

Example - Part Number

F2-RB50-5/16-18x1.000



Open (Thru)



Closed (Blind)

Thread	Common Thread Lengths - Inch									
4-40	0.250	0.375	0.500	0.625	0.750	0.875	1.000	1.250	1.500	2.000
6-32	0.250	0.375	0.500	0.625	0.750	0.875	1.000	1.250	1.500	2.000
8-32	0.250	0.375	0.500	0.625	0.750	0.875	1.000	1.250	1.500	2.000
10-24	0.250	0.375	0.500	0.625	0.750	0.875	1.000	1.250	1.500	2.000
10-32	0.250	0.375	0.500	0.625	0.750	0.875	1.000	1.250	1.500	2.000
1/4-20	0.250	0.375	0.500	0.625	0.750	0.875	1.000	1.250	1.500	2.000
1/4-28	0.250	0.375	0.500	0.625	0.750	0.875	1.000	1.250	1.500	2.000
5/16-18	0.250	0.375	0.500	0.625	0.750	0.875	1.000	1.250	1.500	2.000
3/8-16	0.250	0.375	0.500	0.625	0.750	0.875	1.000	1.250	1.500	2.000
7/16-20	0.250	0.375	0.500	0.625	0.750	0.875	1.000	1.250	1.500	2.000
1/2-13	0.250	0.375	0.500	0.625	0.750	0.875	1.000	1.250	1.500	2.000
5/8-11	0.250	0.375	0.500	0.625	0.750	0.875	1.000	1.250	1.500	2.000
3/4-10	0.250	0.375	0.500	0.625	0.750	0.875	1.000	1.250	1.500	2.000

* Grayed-out sizes are not recommended with shown baseplate

Plating	TZP (Trivalent Zinc)	Zinc-Nickel	Nano	E-Coat	Grades	303	304	316
Other plating and coating options available					* Grayed-out sizes are not recommended with shown baseplate			

All plating and materials offered are RoHS and REACH Compliant

Availability

Many common sizes in stock. Call for availability.

A Rotaloc® Representative will be happy to discuss your specific application and product specifications.

Contact Rotaloc®

Contact Us:

Tel (303) 948-5434 or Toll Free (888) Rotaloc or (888)-768-2562
www.rotaloc.com | info@rotaloc.com

Address

Rotaloc International, LLC
 9903 Titan Court, Suite #15, Littleton, CO 80125 - USA

Value - Quality - Service



F2-RB76 Inch Threads

Bonding Fasteners

Rotaloc International, LLC

Sample Image



As Shown: F2-RB76-1/2-13x0.500

F2



Female Threaded Collar

RB76


76 Millimeter Round Baseplate

Example - Part Number

F2-RB76-1/2-13x0.500



Open (Thru)



Closed (Blind)

Thread	Common Thread Lengths - Inch									
4-40	0.250	0.375	0.500	0.625	0.750	0.875	1.000	1.250	1.500	2.000
6-32	0.250	0.375	0.500	0.625	0.750	0.875	1.000	1.250	1.500	2.000
8-32	0.250	0.375	0.500	0.625	0.750	0.875	1.000	1.250	1.500	2.000
10-24	0.250	0.375	0.500	0.625	0.750	0.875	1.000	1.250	1.500	2.000
10-32	0.250	0.375	0.500	0.625	0.750	0.875	1.000	1.250	1.500	2.000
1/4-20	0.250	0.375	0.500	0.625	0.750	0.875	1.000	1.250	1.500	2.000
1/4-28	0.250	0.375	0.500	0.625	0.750	0.875	1.000	1.250	1.500	2.000
5/16-18	0.250	0.375	0.500	0.625	0.750	0.875	1.000	1.250	1.500	2.000
3/8-16	0.250	0.375	0.500	0.625	0.750	0.875	1.000	1.250	1.500	2.000
7/16-20	0.250	0.375	0.500	0.625	0.750	0.875	1.000	1.250	1.500	2.000
1/2-13	0.250	0.375	0.500	0.625	0.750	0.875	1.000	1.250	1.500	2.000
5/8-11	0.250	0.375	0.500	0.625	0.750	0.875	1.000	1.250	1.500	2.000
3/4-10	0.250	0.375	0.500	0.625	0.750	0.875	1.000	1.250	1.500	2.000

* Grayed-out sizes are not recommended with shown baseplate

Plating	TZP (Trivalent Zinc)	Zinc-Nickel	Nano	E-Coat	Grades	303	304	316
Other plating and coating options available					* Grayed-out sizes are not recommended with shown baseplate			

All plating and materials offered are RoHS and REACH Compliant

Availability

Many common sizes in stock. Call for availability.

A Rotaloc® Representative will be happy to discuss your specific application and product specifications.

Contact Rotaloc®

Contact Us:

Tel (303) 948-5434 or Toll Free (888) Rotaloc or (888)-768-2562
www.rotaloc.com | info@rotaloc.com

Address

Rotaloc International, LLC
 9903 Titan Court, Suite #15, Littleton, CO 80125 - USA

Value - Quality - Service



F2-SB15 Inch Thread Bonding Fasteners

Rotaloc International, LLC

Sample Image



As Shown: F2-SB15-1/4-20x0.500

F2




Female Threaded Collar

SB15


15 Millimeter Square Baseplate

Example - Part Number

F2-SB15-1/4-20x0.500



Open (Thru)



Closed (Blind)

Thread	Common Thread Lengths - Inch									
4-40	0.250	0.375	0.500	0.625	0.750	0.875	1.000	1.250	1.500	2.000
6-32	0.250	0.375	0.500	0.625	0.750	0.875	1.000	1.250	1.500	2.000
8-32	0.250	0.375	0.500	0.625	0.750	0.875	1.000	1.250	1.500	2.000
10-24	0.250	0.375	0.500	0.625	0.750	0.875	1.000	1.250	1.500	2.000
10-32	0.250	0.375	0.500	0.625	0.750	0.875	1.000	1.250	1.500	2.000
1/4-20	0.250	0.375	0.500	0.625	0.750	0.875	1.000	1.250	1.500	2.000
1/4-28	0.250	0.375	0.500	0.625	0.750	0.875	1.000	1.250	1.500	2.000
5/16-18	0.250	0.375	0.500	0.625	0.750	0.875	1.000	1.250	1.500	2.000
3/8-16	0.250	0.375	0.500	0.625	0.750	0.875	1.000	1.250	1.500	2.000
7/16-20	0.250	0.375	0.500	0.625	0.750	0.875	1.000	1.250	1.500	2.000
1/2-13	0.250	0.375	0.500	0.625	0.750	0.875	1.000	1.250	1.500	2.000
5/8-11	0.250	0.375	0.500	0.625	0.750	0.875	1.000	1.250	1.500	2.000
3/4-10	0.250	0.375	0.500	0.625	0.750	0.875	1.000	1.250	1.500	2.000

* Grayed-out sizes are not recommended with shown baseplate

Plating	TZP (Trivalent Zinc)	Zinc-Nickel	Nano	E-Coat	Grades	303	304	316
Other plating and coating options available					* Grayed-out sizes are not recommended with shown baseplate			

All plating and materials offered are RoHS and REACH Compliant

Availability

Many common sizes in stock. Call for availability.

A Rotaloc® Representative will be happy to discuss your specific application and product specifications.

Contact Rotaloc®

Contact Us:

Tel (303) 948-5434 or Toll Free (888) Rotaloc or (888)-768-2562
www.rotaloc.com | info@rotaloc.com

Address

Rotaloc International, LLC
 9903 Titan Court, Suite #15, Littleton, CO 80125 - USA

Value - Quality - Service



F2-SB30 Inch Thread Bonding Fasteners

Rotaloc International, LLC

Sample Image



As Shown: F2-SB30-5/16-18x1.25

F2




Female Threaded Collar

SB30


30 Millimeter Square Baseplate

Example - Part Number

F2-SB30-5/16-18x1.25



Open (Thru)



Closed (Blind)

Thread	Common Thread Lengths - Inch									
4-40	0.250	0.375	0.500	0.625	0.750	0.875	1.000	1.250	1.500	2.000
6-32	0.250	0.375	0.500	0.625	0.750	0.875	1.000	1.250	1.500	2.000
8-32	0.250	0.375	0.500	0.625	0.750	0.875	1.000	1.250	1.500	2.000
10-24	0.250	0.375	0.500	0.625	0.750	0.875	1.000	1.250	1.500	2.000
10-32	0.250	0.375	0.500	0.625	0.750	0.875	1.000	1.250	1.500	2.000
1/4-20	0.250	0.375	0.500	0.625	0.750	0.875	1.000	1.250	1.500	2.000
1/4-28	0.250	0.375	0.500	0.625	0.750	0.875	1.000	1.250	1.500	2.000
5/16-18	0.250	0.375	0.500	0.625	0.750	0.875	1.000	1.250	1.500	2.000
3/8-16	0.250	0.375	0.500	0.625	0.750	0.875	1.000	1.250	1.500	2.000
7/16-20	0.250	0.375	0.500	0.625	0.750	0.875	1.000	1.250	1.500	2.000
1/2-13	0.250	0.375	0.500	0.625	0.750	0.875	1.000	1.250	1.500	2.000
5/8-11	0.250	0.375	0.500	0.625	0.750	0.875	1.000	1.250	1.500	2.000
3/4-10	0.250	0.375	0.500	0.625	0.750	0.875	1.000	1.250	1.500	2.000

* Grayed-out sizes are not recommended with shown baseplate

Plating	TZP (Trivalent Zinc)	Zinc-Nickel	Nano	E-Coat	Grades	303	304	316
Other plating and coating options available					* Grayed-out sizes are not recommended with shown baseplate			

All plating and materials offered are RoHS and REACH Compliant

Availability

Many common sizes in stock. Call for availability.

A Rotaloc® Representative will be happy to discuss your specific application and product specifications.

Contact Rotaloc®

Contact Us:

Tel (303) 948-5434 or Toll Free (888) Rotaloc or (888)-768-2562
www.rotaloc.com | info@rotaloc.com

Address

Rotaloc International, LLC
 9903 Titan Court, Suite #15, Littleton, CO 80125 - USA

Value - Quality - Service



F2-SB32 Inch Thread Bonding Fasteners

Rotaloc International, LLC

Sample Image



As Shown: F2-SB32-1/4-20x1.000

F2




Female Threaded Collar

SB32


32 Millimeter Square Baseplate

Example - Part Number

F2-SB32-1/4-20x1.000



Open (Thru)



Closed (Blind)

Thread	Common Thread Lengths - Inch									
4-40	0.250	0.375	0.500	0.625	0.750	0.875	1.000	1.250	1.500	2.000
6-32	0.250	0.375	0.500	0.625	0.750	0.875	1.000	1.250	1.500	2.000
8-32	0.250	0.375	0.500	0.625	0.750	0.875	1.000	1.250	1.500	2.000
10-24	0.250	0.375	0.500	0.625	0.750	0.875	1.000	1.250	1.500	2.000
10-32	0.250	0.375	0.500	0.625	0.750	0.875	1.000	1.250	1.500	2.000
1/4-20	0.250	0.375	0.500	0.625	0.750	0.875	1.000	1.250	1.500	2.000
1/4-28	0.250	0.375	0.500	0.625	0.750	0.875	1.000	1.250	1.500	2.000
5/16-18	0.250	0.375	0.500	0.625	0.750	0.875	1.000	1.250	1.500	2.000
3/8-16	0.250	0.375	0.500	0.625	0.750	0.875	1.000	1.250	1.500	2.000
7/16-20	0.250	0.375	0.500	0.625	0.750	0.875	1.000	1.250	1.500	2.000
1/2-13	0.250	0.375	0.500	0.625	0.750	0.875	1.000	1.250	1.500	2.000
5/8-11	0.250	0.375	0.500	0.625	0.750	0.875	1.000	1.250	1.500	2.000
3/4-10	0.250	0.375	0.500	0.625	0.750	0.875	1.000	1.250	1.500	2.000

* Grayed-out sizes are not recommended with shown baseplate

Plating	TZP (Trivalent Zinc)	Zinc-Nickel	Nano	E-Coat	Grades	303	304	316
Other plating and coating options available					* Grayed-out sizes are not recommended with shown baseplate			

All plating and materials offered are RoHS and REACH Compliant

Availability

Many common sizes in stock. Call for availability.

A Rotaloc® Representative will be happy to discuss your specific application and product specifications.

Contact Rotaloc®

Contact Us:

Tel (303) 948-5434 or Toll Free (888) Rotaloc or (888)-768-2562
www.rotaloc.com | info@rotaloc.com

Address

Rotaloc International, LLC
 9903 Titan Court, Suite #15, Littleton, CO 80125 - USA

Value - Quality - Service



F2-SB50 Inch Thread Bonding Fasteners

Rotaloc International, LLC

Sample Image



As Shown: F2-SB50-3/8-16x0.500

F2




Female Threaded Collar

SB50


50 Millimeter Square Baseplate

Example - Part Number

F2-SB50-3/8-16x0.500



Open (Thru)



Closed (Blind)

Thread	Common Thread Lengths - Inch									
4-40	0.250	0.375	0.500	0.625	0.750	0.875	1.000	1.250	1.500	2.000
6-32	0.250	0.375	0.500	0.625	0.750	0.875	1.000	1.250	1.500	2.000
8-32	0.250	0.375	0.500	0.625	0.750	0.875	1.000	1.250	1.500	2.000
10-24	0.250	0.375	0.500	0.625	0.750	0.875	1.000	1.250	1.500	2.000
10-32	0.250	0.375	0.500	0.625	0.750	0.875	1.000	1.250	1.500	2.000
1/4-20	0.250	0.375	0.500	0.625	0.750	0.875	1.000	1.250	1.500	2.000
1/4-28	0.250	0.375	0.500	0.625	0.750	0.875	1.000	1.250	1.500	2.000
5/16-18	0.250	0.375	0.500	0.625	0.750	0.875	1.000	1.250	1.500	2.000
3/8-16	0.250	0.375	0.500	0.625	0.750	0.875	1.000	1.250	1.500	2.000
7/16-20	0.250	0.375	0.500	0.625	0.750	0.875	1.000	1.250	1.500	2.000
1/2-13	0.250	0.375	0.500	0.625	0.750	0.875	1.000	1.250	1.500	2.000
5/8-11	0.250	0.375	0.500	0.625	0.750	0.875	1.000	1.250	1.500	2.000
3/4-10	0.250	0.375	0.500	0.625	0.750	0.875	1.000	1.250	1.500	2.000

* Grayed-out sizes are not recommended with shown baseplate

Plating	TZP (Trivalent Zinc)	Zinc-Nickel	Nano	E-Coat	Grades	303	304	316
Other plating and coating options available					* Grayed-out sizes are not recommended with shown baseplate			

All plating and materials offered are RoHS and REACH Compliant

Availability

Many common sizes in stock. Call for availability.

A Rotaloc® Representative will be happy to discuss your specific application and product specifications.

Contact Rotaloc®

Contact Us:

Tel (303) 948-5434 or Toll Free (888) Rotaloc or (888)-768-2562
www.rotaloc.com | info@rotaloc.com

Address

Rotaloc International, LLC
 9903 Titan Court, Suite #15, Littleton, CO 80125 - USA

Value - Quality - Service



F2-SB50 Inch Thread Bonding Fasteners

Rotaloc International, LLC

Sample Image






As Shown: F2-SB50rw-3/8-16x0.500

F2 Female Threaded Collar

SB50 50 Millimeter Square Baseplate

Example - Part Number

F2-SB50rw-3/8-16x0.500



Open (Thru)

Thread	Common Thread Lengths - Inch									
4-40	0.250	0.375	0.500	0.625	0.750	0.875	1.000	1.250	1.500	2.000
6-32	0.250	0.375	0.500	0.625	0.750	0.875	1.000	1.250	1.500	2.000
8-32	0.250	0.375	0.500	0.625	0.750	0.875	1.000	1.250	1.500	2.000
10-24	0.250	0.375	0.500	0.625	0.750	0.875	1.000	1.250	1.500	2.000
10-32	0.250	0.375	0.500	0.625	0.750	0.875	1.000	1.250	1.500	2.000
1/4-20	0.250	0.375	0.500	0.625	0.750	0.875	1.000	1.250	1.500	2.000
1/4-28	0.250	0.375	0.500	0.625	0.750	0.875	1.000	1.250	1.500	2.000
5/16-18	0.250	0.375	0.500	0.625	0.750	0.875	1.000	1.250	1.500	2.000
3/8-16	0.250	0.375	0.500	0.625	0.750	0.875	1.000	1.250	1.500	2.000
7/16-20	0.250	0.375	0.500	0.625	0.750	0.875	1.000	1.250	1.500	2.000
1/2-13	0.250	0.375	0.500	0.625	0.750	0.875	1.000	1.250	1.500	2.000
5/8-11	0.250	0.375	0.500	0.625	0.750	0.875	1.000	1.250	1.500	2.000
3/4-10	0.250	0.375	0.500	0.625	0.750	0.875	1.000	1.250	1.500	2.000

* Grayed-out sizes are not recommended with shown baseplate

Plating	TZP (Trivalent Zinc)	Zinc-Nickel	Nano	E-Coat	Grades	303	304	316
Other plating and coating options available					* Grayed-out sizes are not recommended with shown baseplate			

All plating and materials offered are RoHS and REACH Compliant

Availability

Many common sizes in stock. Call for availability.

A Rotaloc® Representative will be happy to discuss your specific application and product specifications.

Contact Rotaloc®

Contact Us:

Tel (303) 948-5434 or Toll Free (888) Rotaloc or (888)-768-2562
www.rotaloc.com | info@rotaloc.com

Address

Rotaloc International, LLC
 9903 Titan Court, Suite #15, Littleton, CO 80125 - USA


Value - Quality - Service



F2-T24x11.5 Inch Thread Bonding Fasteners

Rotaloc International, LLC

Sample Image



As Shown: F2-T24x11.5-1/4-20x0.625

F2





Female Threaded Collar

T24x11.5

24x11.5 Millimeter Rectangular Baseplate

Example - Part Number

F2-T24x11.5-1/4-20x0.625



Open (Thru)

Closed (Blind)

Thread	Common Thread Lengths - Inch									
4-40	0.250	0.375	0.500	0.625	0.750	0.875	1.000	1.250	1.500	2.000
6-32	0.250	0.375	0.500	0.625	0.750	0.875	1.000	1.250	1.500	2.000
8-32	0.250	0.375	0.500	0.625	0.750	0.875	1.000	1.250	1.500	2.000
10-24	0.250	0.375	0.500	0.625	0.750	0.875	1.000	1.250	1.500	2.000
10-32	0.250	0.375	0.500	0.625	0.750	0.875	1.000	1.250	1.500	2.000
1/4-20	0.250	0.375	0.500	0.625	0.750	0.875	1.000	1.250	1.500	2.000
1/4-28	0.250	0.375	0.500	0.625	0.750	0.875	1.000	1.250	1.500	2.000
5/16-18	0.250	0.375	0.500	0.625	0.750	0.875	1.000	1.250	1.500	2.000
3/8-16	0.250	0.375	0.500	0.625	0.750	0.875	1.000	1.250	1.500	2.000
7/16-20	0.250	0.375	0.500	0.625	0.750	0.875	1.000	1.250	1.500	2.000
1/2-13	0.250	0.375	0.500	0.625	0.750	0.875	1.000	1.250	1.500	2.000
5/8-11	0.250	0.375	0.500	0.625	0.750	0.875	1.000	1.250	1.500	2.000
3/4-10	0.250	0.375	0.500	0.625	0.750	0.875	1.000	1.250	1.500	2.000

* Grayed-out sizes are not recommended with shown baseplate

Plating	TZP (Trivalent Zinc)	Zinc-Nickel	Nano	E-Coat	Grades	303	304	316
Other plating and coating options available					* Grayed-out sizes are not recommended with shown baseplate			

All plating and materials offered are RoHS and REACH Compliant

Availability

Many common sizes in stock. Call for availability.

A Rotaloc® Representative will be happy to discuss your specific application and product specifications.

Contact Rotaloc®

Contact Us:

Tel (303) 948-5434 or Toll Free (888) Rotaloc or (888)-768-2562
www.rotaloc.com | info@rotaloc.com

Address

Rotaloc International, LLC
 9903 Titan Court, Suite #15, Littleton, CO 80125 - USA


Value - Quality - Service



F2-T38x11.5 Inch Thread Bonding Fasteners

Rotaloc International, LLC

Sample Image



As Shown: F2-T38x11.5-1/4-20x0.750

F2




Female Threaded Collar

T38x11.5

38x11.5 Millimeter Rectangular Baseplate

Example - Part Number

F2-T38x11.5-1/4-20x0.750



Open (Thru)



Closed (Blind)

Thread	Common Thread Lengths - Inch									
4-40	0.250	0.375	0.500	0.625	0.750	0.875	1.000	1.250	1.500	2.000
6-32	0.250	0.375	0.500	0.625	0.750	0.875	1.000	1.250	1.500	2.000
8-32	0.250	0.375	0.500	0.625	0.750	0.875	1.000	1.250	1.500	2.000
10-24	0.250	0.375	0.500	0.625	0.750	0.875	1.000	1.250	1.500	2.000
10-32	0.250	0.375	0.500	0.625	0.750	0.875	1.000	1.250	1.500	2.000
1/4-20	0.250	0.375	0.500	0.625	0.750	0.875	1.000	1.250	1.500	2.000
1/4-28	0.250	0.375	0.500	0.625	0.750	0.875	1.000	1.250	1.500	2.000
5/16-18	0.250	0.375	0.500	0.625	0.750	0.875	1.000	1.250	1.500	2.000
3/8-16	0.250	0.375	0.500	0.625	0.750	0.875	1.000	1.250	1.500	2.000
7/16-20	0.250	0.375	0.500	0.625	0.750	0.875	1.000	1.250	1.500	2.000
1/2-13	0.250	0.375	0.500	0.625	0.750	0.875	1.000	1.250	1.500	2.000
5/8-11	0.250	0.375	0.500	0.625	0.750	0.875	1.000	1.250	1.500	2.000
3/4-10	0.250	0.375	0.500	0.625	0.750	0.875	1.000	1.250	1.500	2.000

* Grayed-out sizes are not recommended with shown baseplate

Plating	TZP (Trivalent Zinc)	Zinc-Nickel	Nano	E-Coat	Grades	303	304	316
Other plating and coating options available					* Grayed-out sizes are not recommended with shown baseplate			

All plating and materials offered are RoHS and REACH Compliant

Availability

Many common sizes in stock. Call for availability.

A Rotaloc® Representative will be happy to discuss your specific application and product specifications.

Contact Rotaloc®

Contact Us:

Tel (303) 948-5434 or Toll Free (888) Rotaloc or (888)-768-2562
www.rotaloc.com | info@rotaloc.com

Address

Rotaloc International, LLC
 9903 Titan Court, Suite #15, Littleton, CO 80125 - USA

Value - Quality - Service



F2-T38x15 Inch Thread Bonding Fasteners

Rotaloc International, LLC

Sample Image



As Shown: F2-T38x15-5/16-18x0.625

F2




Female Threaded Collar

T38x15


38x15 Millimeter Rectangular Baseplate

Example - Part Number

F2-T38x15-5/16-18x0.625



Open (Thru)



Closed (Blind)

Thread	Common Thread Lengths - Inch									
4-40	0.250	0.375	0.500	0.625	0.750	0.875	1.000	1.250	1.500	2.000
6-32	0.250	0.375	0.500	0.625	0.750	0.875	1.000	1.250	1.500	2.000
8-32	0.250	0.375	0.500	0.625	0.750	0.875	1.000	1.250	1.500	2.000
10-24	0.250	0.375	0.500	0.625	0.750	0.875	1.000	1.250	1.500	2.000
10-32	0.250	0.375	0.500	0.625	0.750	0.875	1.000	1.250	1.500	2.000
1/4-20	0.250	0.375	0.500	0.625	0.750	0.875	1.000	1.250	1.500	2.000
1/4-28	0.250	0.375	0.500	0.625	0.750	0.875	1.000	1.250	1.500	2.000
5/16-18	0.250	0.375	0.500	0.625	0.750	0.875	1.000	1.250	1.500	2.000
3/8-16	0.250	0.375	0.500	0.625	0.750	0.875	1.000	1.250	1.500	2.000
7/16-20	0.250	0.375	0.500	0.625	0.750	0.875	1.000	1.250	1.500	2.000
1/2-13	0.250	0.375	0.500	0.625	0.750	0.875	1.000	1.250	1.500	2.000
5/8-11	0.250	0.375	0.500	0.625	0.750	0.875	1.000	1.250	1.500	2.000
3/4-10	0.250	0.375	0.500	0.625	0.750	0.875	1.000	1.250	1.500	2.000

* Grayed-out sizes are not recommended with shown baseplate

Plating	TZP (Trivalent Zinc)	Zinc-Nickel	Nano	E-Coat	Grades	303	304	316
Other plating and coating options available					* Grayed-out sizes are not recommended with shown baseplate			

All plating and materials offered are RoHS and REACH Compliant

Availability

Many common sizes in stock. Call for availability.

A Rotaloc® Representative will be happy to discuss your specific application and product specifications.

Contact Rotaloc®

Contact Us:

Tel (303) 948-5434 or Toll Free (888) Rotaloc or (888)-768-2562
www.rotaloc.com | info@rotaloc.com

Address

Rotaloc International, LLC
 9903 Titan Court, Suite #15, Littleton, CO 80125 - USA

Value - Quality - Service



F2-T38x19 Inch Thread Bonding Fasteners

Rotaloc International, LLC

Sample Image



As Shown: F2-T38x19-3/8-16x0.625

F2




Female Threaded Collar

T38x19


38x19 Millimeter Rectangular Baseplate

Example - Part Number

F2-T38x19-3/8-16x0.625



Open (Thru)



Closed (Blind)

Thread	Common Thread Lengths - Inch									
4-40	0.250	0.375	0.500	0.625	0.750	0.875	1.000	1.250	1.500	2.000
6-32	0.250	0.375	0.500	0.625	0.750	0.875	1.000	1.250	1.500	2.000
8-32	0.250	0.375	0.500	0.625	0.750	0.875	1.000	1.250	1.500	2.000
10-24	0.250	0.375	0.500	0.625	0.750	0.875	1.000	1.250	1.500	2.000
10-32	0.250	0.375	0.500	0.625	0.750	0.875	1.000	1.250	1.500	2.000
1/4-20	0.250	0.375	0.500	0.625	0.750	0.875	1.000	1.250	1.500	2.000
1/4-28	0.250	0.375	0.500	0.625	0.750	0.875	1.000	1.250	1.500	2.000
5/16-18	0.250	0.375	0.500	0.625	0.750	0.875	1.000	1.250	1.500	2.000
3/8-16	0.250	0.375	0.500	0.625	0.750	0.875	1.000	1.250	1.500	2.000
7/16-20	0.250	0.375	0.500	0.625	0.750	0.875	1.000	1.250	1.500	2.000
1/2-13	0.250	0.375	0.500	0.625	0.750	0.875	1.000	1.250	1.500	2.000
5/8-11	0.250	0.375	0.500	0.625	0.750	0.875	1.000	1.250	1.500	2.000
3/4-10	0.250	0.375	0.500	0.625	0.750	0.875	1.000	1.250	1.500	2.000

* Grayed-out sizes are not recommended with shown baseplate

Plating	TZP (Trivalent Zinc)	Zinc-Nickel	Nano	E-Coat	Grades	303	304	316
Other plating and coating options available					* Grayed-out sizes are not recommended with shown baseplate			

All plating and materials offered are RoHS and REACH Compliant

Availability

Many common sizes in stock. Call for availability.

A Rotaloc® Representative will be happy to discuss your specific application and product specifications.

Contact Rotaloc®

Contact Us:

Tel (303) 948-5434 or Toll Free (888) Rotaloc or (888)-768-2562
www.rotaloc.com | info@rotaloc.com

Address

Rotaloc International, LLC
 9903 Titan Court, Suite #15, Littleton, CO 80125 - USA

Value - Quality - Service



F2-T40x10 Inch Thread Bonding Fasteners

Rotaloc International, LLC

Sample Image



As Shown: F2-T40x10-10-32x0.625

F2




Female Threaded Collar

T40x10


40x10 Millimeter Rectangular Baseplate

Example - Part Number

F2-T40x10-10-32x0.625



Open (Thru)



Closed (Blind)

Thread	Common Thread Lengths - Inch									
4-40	0.250	0.375	0.500	0.625	0.750	0.875	1.000	1.250	1.500	2.000
6-32	0.250	0.375	0.500	0.625	0.750	0.875	1.000	1.250	1.500	2.000
8-32	0.250	0.375	0.500	0.625	0.750	0.875	1.000	1.250	1.500	2.000
10-24	0.250	0.375	0.500	0.625	0.750	0.875	1.000	1.250	1.500	2.000
10-32	0.250	0.375	0.500	0.625	0.750	0.875	1.000	1.250	1.500	2.000
1/4-20	0.250	0.375	0.500	0.625	0.750	0.875	1.000	1.250	1.500	2.000
1/4-28	0.250	0.375	0.500	0.625	0.750	0.875	1.000	1.250	1.500	2.000
5/16-18	0.250	0.375	0.500	0.625	0.750	0.875	1.000	1.250	1.500	2.000
3/8-16	0.250	0.375	0.500	0.625	0.750	0.875	1.000	1.250	1.500	2.000
7/16-20	0.250	0.375	0.500	0.625	0.750	0.875	1.000	1.250	1.500	2.000
1/2-13	0.250	0.375	0.500	0.625	0.750	0.875	1.000	1.250	1.500	2.000
5/8-11	0.250	0.375	0.500	0.625	0.750	0.875	1.000	1.250	1.500	2.000
3/4-10	0.250	0.375	0.500	0.625	0.750	0.875	1.000	1.250	1.500	2.000

* Grayed-out sizes are not recommended with shown baseplate

Plating	TZP (Trivalent Zinc)	Zinc-Nickel	Nano	E-Coat	Grades	303	304	316
Other plating and coating options available					* Grayed-out sizes are not recommended with shown baseplate			

All plating and materials offered are RoHS and REACH Compliant

Availability

Many common sizes in stock. Call for availability.

A Rotaloc® Representative will be happy to discuss your specific application and product specifications.

Contact Rotaloc®

Contact Us:

Tel (303) 948-5434 or Toll Free (888) Rotaloc or (888)-768-2562
www.rotaloc.com | info@rotaloc.com

Address

Rotaloc International, LLC
 9903 Titan Court, Suite #15, Littleton, CO 80125 - USA

Value - Quality - Service



F2-T50x15 Inch Thread Bonding Fasteners

Rotaloc International, LLC

Sample Image



As Shown: F2-T50x15-10-32x0.625

F2




Female Threaded Collar

T50x15


50x15 Millimeter Rectangular Baseplate

Example - Part Number

F2-T50x15-10-32x0.625



Open (Thru)



Closed (Blind)

Thread	Common Thread Lengths - Inch									
4-40	0.250	0.375	0.500	0.625	0.750	0.875	1.000	1.250	1.500	2.000
6-32	0.250	0.375	0.500	0.625	0.750	0.875	1.000	1.250	1.500	2.000
8-32	0.250	0.375	0.500	0.625	0.750	0.875	1.000	1.250	1.500	2.000
10-24	0.250	0.375	0.500	0.625	0.750	0.875	1.000	1.250	1.500	2.000
10-32	0.250	0.375	0.500	0.625	0.750	0.875	1.000	1.250	1.500	2.000
1/4-20	0.250	0.375	0.500	0.625	0.750	0.875	1.000	1.250	1.500	2.000
1/4-28	0.250	0.375	0.500	0.625	0.750	0.875	1.000	1.250	1.500	2.000
5/16-18	0.250	0.375	0.500	0.625	0.750	0.875	1.000	1.250	1.500	2.000
3/8-16	0.250	0.375	0.500	0.625	0.750	0.875	1.000	1.250	1.500	2.000
7/16-20	0.250	0.375	0.500	0.625	0.750	0.875	1.000	1.250	1.500	2.000
1/2-13	0.250	0.375	0.500	0.625	0.750	0.875	1.000	1.250	1.500	2.000
5/8-11	0.250	0.375	0.500	0.625	0.750	0.875	1.000	1.250	1.500	2.000
3/4-10	0.250	0.375	0.500	0.625	0.750	0.875	1.000	1.250	1.500	2.000

* Grayed-out sizes are not recommended with shown baseplate

Plating	TZP (Trivalent Zinc)	Zinc-Nickel	Nano	E-Coat	Grades	303	304	316
Other plating and coating options available					* Grayed-out sizes are not recommended with shown baseplate			

All plating and materials offered are RoHS and REACH Compliant

Availability

Many common sizes in stock. Call for availability.

A Rotaloc® Representative will be happy to discuss your specific application and product specifications.

Contact Rotaloc®

Contact Us:

Tel (303) 948-5434 or Toll Free (888) Rotaloc or (888)-768-2562
www.rotaloc.com | info@rotaloc.com

Address

Rotaloc International, LLC
 9903 Titan Court, Suite #15, Littleton, CO 80125 - USA

Value - Quality - Service



F2-T76x38 Inch Thread Bonding Fasteners

Rotaloc International, LLC

Sample Image



As Shown: F2-T76x38-5/16-18x1.000

F2




Female Threaded Collar

T76x38


76x38 Millimeter Rectangular Baseplate

Example - Part Number

F2-T76x38-5/16-18x1.000



Open (Thru)



Closed (Blind)

Thread	Common Thread Lengths - Inch									
4-40	0.250	0.375	0.500	0.625	0.750	0.875	1.000	1.250	1.500	2.000
6-32	0.250	0.375	0.500	0.625	0.750	0.875	1.000	1.250	1.500	2.000
8-32	0.250	0.375	0.500	0.625	0.750	0.875	1.000	1.250	1.500	2.000
10-24	0.250	0.375	0.500	0.625	0.750	0.875	1.000	1.250	1.500	2.000
10-32	0.250	0.375	0.500	0.625	0.750	0.875	1.000	1.250	1.500	2.000
1/4-20	0.250	0.375	0.500	0.625	0.750	0.875	1.000	1.250	1.500	2.000
1/4-28	0.250	0.375	0.500	0.625	0.750	0.875	1.000	1.250	1.500	2.000
5/16-18	0.250	0.375	0.500	0.625	0.750	0.875	1.000	1.250	1.500	2.000
3/8-16	0.250	0.375	0.500	0.625	0.750	0.875	1.000	1.250	1.500	2.000
7/16-20	0.250	0.375	0.500	0.625	0.750	0.875	1.000	1.250	1.500	2.000
1/2-13	0.250	0.375	0.500	0.625	0.750	0.875	1.000	1.250	1.500	2.000
5/8-11	0.250	0.375	0.500	0.625	0.750	0.875	1.000	1.250	1.500	2.000
3/4-10	0.250	0.375	0.500	0.625	0.750	0.875	1.000	1.250	1.500	2.000

* Grayed-out sizes are not recommended with shown baseplate

Plating	TZP (Trivalent Zinc)	Zinc-Nickel	Nano	E-Coat	Grades	303	304	316
Other plating and coating options available					* Grayed-out sizes are not recommended with shown baseplate			

All plating and materials offered are RoHS and REACH Compliant

Availability

Many common sizes in stock. Call for availability.

A Rotaloc® Representative will be happy to discuss your specific application and product specifications.

Contact Rotaloc®

Contact Us:

Tel (303) 948-5434 or Toll Free (888) Rotaloc or (888)-768-2562
www.rotaloc.com | info@rotaloc.com

Address

Rotaloc International, LLC
 9903 Titan Court, Suite #15, Littleton, CO 80125 - USA

Value - Quality - Service



F2-HP44 Inch Thread Bonding Fasteners

Rotaloc International, LLC

Sample Image



As Shown: F2-HP44-1/4-20x0.625

F2




Female Threaded Collar

HP44


44 Millimeter Homeplate Like Baseplate

Example - Part Number

F2-HP44-1/4-20x0.625



Open (Thru)



Closed (Blind)

Thread	Common Thread Lengths - Inch									
4-40	0.250	0.375	0.500	0.625	0.750	0.875	1.000	1.250	1.500	2.000
6-32	0.250	0.375	0.500	0.625	0.750	0.875	1.000	1.250	1.500	2.000
8-32	0.250	0.375	0.500	0.625	0.750	0.875	1.000	1.250	1.500	2.000
10-24	0.250	0.375	0.500	0.625	0.750	0.875	1.000	1.250	1.500	2.000
10-32	0.250	0.375	0.500	0.625	0.750	0.875	1.000	1.250	1.500	2.000
1/4-20	0.250	0.375	0.500	0.625	0.750	0.875	1.000	1.250	1.500	2.000
1/4-28	0.250	0.375	0.500	0.625	0.750	0.875	1.000	1.250	1.500	2.000
5/16-18	0.250	0.375	0.500	0.625	0.750	0.875	1.000	1.250	1.500	2.000
3/8-16	0.250	0.375	0.500	0.625	0.750	0.875	1.000	1.250	1.500	2.000
7/16-20	0.250	0.375	0.500	0.625	0.750	0.875	1.000	1.250	1.500	2.000
1/2-13	0.250	0.375	0.500	0.625	0.750	0.875	1.000	1.250	1.500	2.000
5/8-11	0.250	0.375	0.500	0.625	0.750	0.875	1.000	1.250	1.500	2.000
3/4-10	0.250	0.375	0.500	0.625	0.750	0.875	1.000	1.250	1.500	2.000

* Grayed-out sizes are not recommended with shown baseplate

Plating	TZP (Trivalent Zinc)	Zinc-Nickel	Nano	E-Coat	Grades	303	304	316
Other plating and coating options available					* Grayed-out sizes are not recommended with shown baseplate			

All plating and materials offered are RoHS and REACH Compliant

Availability

Many common sizes in stock. Call for availability.

A Rotaloc® Representative will be happy to discuss your specific application and product specifications.

Contact Rotaloc®

Contact Us:

Tel (303) 948-5434 or Toll Free (888) Rotaloc or (888)-768-2562
www.rotaloc.com | info@rotaloc.com

Address

Rotaloc International, LLC
 9903 Titan Court, Suite #15, Littleton, CO 80125 - USA

Value - Quality - Service