

F1-RB23




F1-RB38




M1-RB23




M1-RB38



M1-RB23



M1-RB38



**All materials are RoHS and REACH compliant*

***Additional and custom sizes and configurations available*

Peel-and-stick **Very High Bond (VHB) Adhesive** makes for quick and easy installation providing high strength, non-destructive mounting options for use in a variety of applications, including:

- Electrical Systems
- Automotive
- Composites
- Appliance
- Marine Crafts/Equipment
- Home Renovation
- Office and Furniture
- Transportation
- Agricultural Equipment
- Medical Equipment
- ...and many more.

Contact **Rotaloc** today and our team will gladly help find the right fastener for your application.

Standard Inventory Sizes

Part No.	Thread Style	Baseplate Style	Thread Size	Thread Length	Price (ea.)
M1-RB23#3-VHB-M6x20mm	Male Stud	RB23#3 (23mm Round)	M6	20mm	\$1.25
M1-RB23#3-VHB-1/4-20x0.750	Male Stud	RB23#3 (23mm Round)	1/4-20	0.750"	\$1.25
M1-RB38#3-VHB-1/4-20x1.00	Male Stud	RB38#3 (38mm Round)	1/4-20	1.00"	\$1.35
M1-RB38#3-VHB-M6x25mm	Male Stud	RB38#3 (38mm Round)	M6	25mm	\$1.35
F1-RB23#3-VHB-1/4-20 (SQ-Nut)	Female Nut	RB23#3 (23mm Round)	1/4-20	---	\$1.10
F1-RB23#3-VHB-M6 (SQ-Nut)	Female Nut	RB23#3 (23mm Round)	M6	---	\$1.10
F1-RB38#3-VHB-1/4-20 (SQ-Nut)	Female Nut	RB38#3 (38mm Round)	1/4-20	---	\$1.15
F1-RB38#3-VHB-M6 (SQ-Nut)	Female Nut	RB38#3 (38mm Round)	M6	---	\$1.15

Additional and custom sizes and configurations available

Installation



1. Prepare surface



2. Peel vinyl backing



3. Stick to prepared surface

Very High Bond (VHB) Properties

Property	Values
90° Peel Adhesion (Backing: 5mil AL foil)	22 lb/in
90° Peel Adhesion (Backing: 2mil AL foil)	39 N/cm
Normal Tensile Strength	480 kPa (70 lb/in²)
Overlap Shear Strength	550 kPa (80 lb/in²)
Short Term Temperature Resistance	149° C (300° F)
Long Term Temperature Resistance	93° C (200° F)
Minimum Application Temperature	10° C (50° F)
Static Shear @ 23° C (73°F), (0.5in²)	1000 g
Static Shear @ 66° C (150°F), (0.5in²)	500 g
Static Shear @ 93° C (200°F), (0.5in²)	250 g

- Designed for medium-intensity applications
- Bonds to nearly any surface/material
- VHB Adhesive creates a watertight seal
- RoHS and REACH compliant



Contact **Rotaloc** today and our team will gladly help find the right fastener for your application.